



AF7125A

FOIL-SCRIM-KRAFT TAPE

PRODUCT DESCRIPTION

3-Way Foil-Scrim-Kraft backing, combined with a transparent high performance solvent acrylic adhesive, protected by an easy-release silicone release paper.

FEATURES

3-Way Foil-Scrim-Kraft backing provides excellent reflection of both heat and light.
High quality adhesive with super strong adhesion and holding power offers reliable and durable Foil-Scrim-Kraft Facing joints and seams sealing in HVAC ductwork application.
Low moisture vapour transmission rate makes ProTack Tape AF7125A an excellent vapour barrier
Service Temperature range from -30 ~ +80 C (-22~ +176 F).

TYPICAL PHYSICAL PROPERTIES

PROPERTIES	METRIC	ENGLISH	TEST METHOD
Backing Thickness	120 Micron	4.8 Mil	PSTC-133 / ASTM D 3652
Total Thickness	170 Micron	6.8 Mil	PSTC-133 / ASTM D 3652
Adhesion to Steel	25 N/25mm	90 Oz./In.	PSTC-101 / ASTM D 3330
Tack Rolling Ball	15 cm	6.0 In.	PSTC-6 / ASTM D 3121
Tensile Strength	120 N/25mm	27.3 Lb/In.	PSTC-131 / ASTM D 3759
Elongation	%	1.0	PSTC-131 / ASTM D 3759
Service Temperature	-30 ~ +80 C	-22 ~ + 176 F	-----
Applying Temperature	+10 ~ 40 C	+50 ~ + 105 F	-----
Flame Spread / Smoke Develped	Smoke: 5	Flame: 5	ASTM E84-08 CAN\ULC S102-7

TYPICAL APPLICATIONS: HVAC industry for joining and sealing Foil-Scrim-Kraft Facing laminated fiberglass blanket / duct board joints and seams; joining and sealing flexible air duct seams and connections. May also be used for other industrial uses requiring a tape with these characteristics and benefits.

PRODUCT FORM & SIZE AVAILABLE

Cut Roll: 50mm (2") / 63mm (2.5") / 75mm (3") / 100mm (4")
Roll: 1200mm x 50m

STORAGE & SHELF LIFE: 12 months when stored at 21 C (70F) / 50% relative humidity out of direct sunlight.

SURFACE PREPERATION: It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean,dry,free of grease, oil or other contaminants.

PRODUCT USE: It is essential that the user evaluate the ProTack product to determine whether it is fit for a particular purpose and user’s method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on the ProTack Tape product.

LIMITED WARRANTY & LIMITED REMEDY: Your exclusive remedy and **ProTack Tape** obligation shall be at **ProTack Tape’s** option, to replace or repair the **ProTack** product or refund the purchase price of the **ProTack** product.

19131 – 21st Avenue, Surrey, B.C., Canada, V3S 3M3
Bus: 604.535.7272 Fax: 604.535.7279 Toll Free: 866.91FROST (37678)

“WE HAVE YOU COVERED”