

1525CW

FSK INSULATION TAPE

Venture Tape 1525CW COLD WEATHER FSK is a 5.0 mil (125 μ m) foil/scrim/kraft (FSK) lamination coated with Venture's CW cold weather solvent acrylic pressure sensitive adhesive. Versatile FSK applies easily to both fibrous and sheet metal ducts and easily conforms to irregular surfaces. Venture Tape 1525CW excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.

Features & Benefits

UL723 Listed

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	5.0 mils	127.0 microns
Thickness Adhesive Exposed	1.5 mils	38.1 microns
Thickness Liner	3.1 mils	78.7 microns
Peel Adhesion Exposed	96 oz/inch width	26.7 N/25 mm
Shear Strength Exposed	>168 hrs	>168 hrs
Tensile Strength	40 lbs/inch width	178 N/25 mm
Elongation	2%	2%
Minimum Appl	-35 degrees F	-37 degrees C
Maximum Use Temp	260 degrees F	127 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045