

1540CW

ASJ INSULATION TAPE

Venture Tape 1540CW COLD WEATHER ASJ is a 9.7 mil (125 μ m) white kraft paper/scrim/foil (ASJ) lamination coated with Venture's CW cold weather solvent acrylic pressure sensitive adhesive. Specifically designed for use as a vapor seal on ASJ faced duct board and pipe insulation, Venture Tape 1540CW applies easily and excels in demanding temperature and humidity applications, providing superior performance and durability over a wide range of conditions. The facing used on Venture Tape 1540CW meets ASTM C1136, Type I, II, III, IV.

Features & Benefits

Specifically designed for cold weather conditions

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	9.7 mils	246.4 microns
Thickness Adhesive Exposed	1.8 mils	45.7 microns
Thickness Liner	3.1 mils	78.7 microns
Peel Adhesion Exposed	92 oz/inch width	26.6 N/25 mm
Shear Strength Exposed	>168 hrs	>168 hrs
Tensile Strength	40 lbs/inch width	178 N/25 mm
Elongation	2%	2%
Minimum Appl	-35 degrees F	-37 degrees C
Maximum Use Temp	300 degrees F	149 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample
Toll Free North America 800-343-1076
From United Kingdom 0-800-962-957
From Australia 1-800-122-797
www.venturetape.com
www.boma.it



USA
Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065
www.venturetape.com

Europe - Venture Tape
Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 8RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia
Venture Tape Australasia, Pty., Ltd.
11B Production Drive
Campbellfield, VIC 3061
Australia
(03) 9357 6025
FAX (03) 9357 6045